


# TintCrete

 Products Made in the USA by JE Tomes, an American Owned and Operated Company

## TINTCRETE RESURFACER

Color tinted polymer modified resurfacing mortar



**Repair Thickness**  
Featheredge to ¼"



**Set Time**  
1 Hour



**Application Technique**  
Trowel, Brush, Spray

## Description

**TintCrete Resurfacer** is a 1 component, polymer modified, high performance concrete repair and resurfacing mortar. **TintCrete Resurfacer** is available in 2 standard colors – Old Concrete and New Concrete. It is simply mixed with water and applied from featheredge to ¼" thick in one application. Apply horizontal, vertical or overhead. Product sets in approximately 1 hour and is ready for light traffic in 6 to 8 hours at 70 degrees Fahrenheit when broomed or brushed.

## Dependable and Durable

- Long working time
- Polymer modified
- Portland Cement based
- Apply by trowel, broom, brush or spray
- One component – just add water
- 2 standard colors – Old Concrete and New Concrete

## Where to Use

- Concrete Resurfacing
- Driveways, sidewalks
- Concrete patching up to ¼" thick
- Balconies, parking garages
- Interior or exterior
- Resurface pitted concrete

## Components

**TintCrete Resurfacer** is a special blend of cements, aggregates and exclusive modifiers. Designed for general purpose and high performance concrete repair or resurfacing applications.

## Application

Trowel or broom apply. Rub or scratch part of the mixed material onto surface just prior to application. For finer finishing use a concrete finishers broom For thickness over ¼" apply in multiple applications, allowing material to dry between each application.

## Packaging and Yield

Unit Size	Approx. Yield
1 quart	6 sq. ft
10 lb pail	20 sq. ft.
50 lb pail	100 sq. ft. @ 1/16" thickness